

1. General description

Powerful solvent blend to remove gum, carbon and sludge from carburettors, EGR, PCV and throttle valves in combustion engines



2. Features

- Quickly dissolves carburettor deposits, providing faster starting and smooth idling.
- Dissolves soot, gum, carbon and oil deposits.
- None chlorinated solvents.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Carburettor components.
- Positive Crankcase Venting (PCV) systems and valves.
- Exhaust Gas Recycling (EGR) valves.
- Throttle valve.

4. Directions

- Dismount and wet the contaminated surfaces and allow to act for 5 min. Repeat if needed. Allow the EGR and PCV valve to dry before re-assembling. Start engine at idle. Spray the throttle valve again and accelerate the engine with a couple of short impulses to 2000 rpm.



Technical data sheet Carb & EGR Cleaner

Reference : 10165

Carburettor cleaning:

- Stop engine and let it cool down. Remove air filter.
- Spray sparingly into carburettor, wetting all visible parts.
- Spray exterior surfaces until they are clean and allow to dry.
- Start engine. Whilst running at medium idle, spray directly into air intake. Accelerate.
- Stop engine. Lubricate and protect exterior parts and linkages with CRC 5-56.
- Put filter back into place and, if necessary, adjust air-fuel ratio
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

	Aerosol	Bulk
Appearance	Liquid.	Liquid.
Color	Colorless.	Colorless.
Odor	Aromatic.	Aromatic.
Density	0.832 g/cm ³ (@ 20°C).	0.832 g/cm ³ (@ 20°C).
Flash Point	< 0 °C (Closed Cup)	< 0 °C
Auto Ignition temperature	> 200 °C	> 200 °C
Vapor density	3.3 (@ 20°C).	3.3 (@ 20°C).
Viscosity	0.65 mPa.s (@ 20°C).	0.65 mPa.s (@ 20°C).
Kauri Butanol value active product	> 15000	> 15000

6. Packaging

Aerosol	12x300 ML	Ref. : 30491
	6x300 ML	Ref. : 30491

7. Remarks

- If spilled or sprayed on painted surfaces, rubber or sensitive plastics, wipe or wash off immediately.
- Always follow the recommendations in the instruction manual provided by the equipment manufacturer.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





Technical data sheet
Carb & EGR Cleaner

Reference : 10165

this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_RED-CARBURETTOR_CLEANER-20140522

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

3/1

