

# CERAMIC PASTE PRO

---

## Technical Data Sheet

---

Product name: Ceramic Paste Pro  
Sales code: 32711

Creation date: 8/2016

Version: I

---

### 1: General description

Universal, ceramic assembly paste for anti seize applications. No potential for galvanic corrosion and protects for burning-in. Facilitates disassembly after thermal stress (-40°C to 1400°C).

### 2: Features

- Enables easy disassembly of threaded parts, gaskets and flanges, even after a long time of too high pressure and high temperature
- Protects against burning-in, corrosion and seizing
- Stops and prevents disc brake noise and vibration
- None chlorinated solvents
- Totally free of lead and chromates
- Excellent water resistance
- Functional over a wide temperature range

### 3: Applications

- Sound deadening mass for squeaking brakes
- Flange connections under high temperature conditions
- Pin or spline connections
- Threaded connections

### 4: Directions

- Apply to a clean, dry surface
- Apply a thin even film
- Do not mix with other products
- Do not use on energized equipment
- Use only with adequate ventilation
- To remove residues or excess product, use Power Clean Pro
- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products



## 5: Typical product data (without propellant)

- Appearance : Paste.
- Color : White
- Odor : Perceptible odour
- Flash Point : >200 °C (open cup)
- Density : 1.419 g/cm<sup>3</sup> (@ 20°C)
- Operating temperature active product : -40-->+1400 °C
- 4-ball weld load active product : 3800 N
- NLGI class : 3

## 6: Packaging

Aerosol

12x250 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.