



## 1. General description

Slow moving spindles for force transfer and linear antifriction bearings.

## 2. Features

- Excellent water resistance.
- Functional over a wide temperature range.
- Produces a very low coefficient of friction.
- Reduces stick and slip problems.
- Provides long lasting lubrication.
- Does not run or drip off.
- Prevents seizing and fretting.
- High EP (Extreme Pressure)- and antiwear-properties.

## 3. Applications

- Guide rails.
- Slides.
- Slow moving spindles for power transfer.

## 4. Directions

- Shake well before use.
- Use only with adequate ventilation.
- Do not use on energized equipment.
- Apply to a clean, dry surface.
- Apply the quantity as described by the machine manufacturer.
- Do not mix with other products.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

## 5. Typical product data (without propellant)

Appearance

Grease.



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
**www.crcind.com**



