

MOLYKOTE® G-5511 Compound

Compound based on silicone oil and thickened with PTFE

Features & benefits

- Excellent water resistance
- Wide service temperature range from -40 to 200°C
- Compatible with many elastomers
- Lubrication of ceramics and plastics in water taps
- Meets requirements of EN 817
- Meets several global standards for drinking water contact

Composition

- Silicone oil
- PTFE

Applications

Designed for application in water taps between ceramic discs, rubber gaskets and plastic components. Suitable for gas applications.

Description

MOLYKOTE® G-5511 Compound is a silicone-based lubricant designed for application in water taps and gas valves. MOLYKOTE® G-5511 Compound meets several global standards for water contact: complies with UBA guidelines for the hygienic assessment of lubricants with drinking water contact, with the requirements of the Water Regulation Advisory Scheme (BS6920:2000), ACS, NSF/ANSI 61 Standard and DVGW gas certification. It is suitable for use with hot water (up to 85°C) and cold water.

How to use

MOLYKOTE® G-5511 Compound can be applied by hand, automated equipment or brushing.

Handling precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION.

Typical properties

Specification writers: These values are not intended for use in preparing specifications. Please contact your local MOLYKOTE® sales representative prior to writing specifications on this product.

Standard ⁽¹⁾	Test	Unit	Result
	Color		White
CTM 0191	Penetration, unworked	mm/10	320
DIN 51 818	NLGI class		1-2
DIN 51808	Oxidation resistance, 100 h/99°C	mbar	0
DIN 51807	Water resistance, 90°C/7 days		0
DIN 51757	Density, 20°C	g/ml	1.3

⁽¹⁾CTM: Corporate Test Methods; copies of CTMs are available on request. DIN: Deutsche Industrie Norm.

Usable life and storage

MOLYKOTE® G-5511 Compound can be stored for 60 months from date of manufacture at ambient temperatures in its original, closed container.

Packaging

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest MOLYKOTE® sales office or MOLYKOTE® distributor.

*DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.
© 2015-2019 DuPont.*

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.